

ZPMV2.E188069
Wiring, Printed - Component

PRINTEC CIRCUIT ELECTRONIC CO LTD


E188069

3rd Fl
33-19 Shou Shan Rd
Hsin Chuang District
New Taipei, 242 TAIWAN

	Cond Width				Max			Max			
		Min	Cond	SS/	Area	Solder		Oper		Meets	C
	Min	Edge	Thk	DS/	Diam	Limits		Temp	Flame	UL796	T
Type	mm(in)	mm(in)	mic(mil)	DSO	mm(in)	C	sec	C	Class	DSR	I
Multilayer printed wiring boards.											
M28V0	0.08(0.003)	0.18(0.007)	17(0.67) Int:35	DS	76.2(3.0)	280	10	105	V-0	All	*
M28V0HF	0.08(0.003)	0.18(0.007)	17(0.67) Int:35	DS	76.2(3.0)	280	10	105	V-0	All	*
MLV0	0.1(0.004)	0.2(0.008)	17(0.67) Int:70	DS	76.2(3.0)	280	10	130	V-0	All	3
Multilayer printed wiring boards, flammability only Recognition.											
22V0 @	-	-	-	DS	-	260	10	-	V-0	-	-
Single Layer Metal Base Printed Wiring Board, flammability only recognition.											
AL01	-	-	-	SS	-	288	20	-	V-0	-	-
AL02	-	-	-	SS	-	288	20	-	V-0	-	-
Single layer printed wiring boards.											
10HB	0.15(0.006)	0.23(0.009)	34(1.34)	DS	25.4(1.0)	260	10	105	HB	All	-
11V0	0.15(0.006)	0.23(0.009)	34(1.34)	DS	25.4(1.0)	260	10	105	V-0	All	-
12V0	0.1(0.004)	0.2(0.008)	17(0.67)	DS	25.4(1.0)	274	15	130	V-0	All	*
12V0HF	0.1(0.004)	0.2(0.008)	17(0.67)	DS	25.4(1.0)	274	15	130	V-0	All	*

@ - Employed with silver and carbon paste crossover conductors.

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or trademark  or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2017-11-16